

Configuring server port or bind address

You can change the port your Unimus server runs on.
You can also change the server bind-address if necessary.

By default, Unimus bind to all IP addresses on all adapters.
Default port is 8085 (or configured Tomcat port if running in Tomcat).

On Windows:

For portable:

Create a file named **Unimus.I4j.ini** in the same directory as the Unimus executable.
Change **Unimus** in the above file name to exactly match the name of the Unimus executable.

For installer:

Add the below lines to **Unimus.I4j.ini** in 'C:\Program Files\Unimus\'.
Inside of this configuration file, please add the following lines:

```
-Dserver.address=<your_ip>  
-Dserver.port=<port>
```

Please make sure to place each argument into its own line.
Insert proper values behind each configuration argument.

If you only want to configure a single parameter, please omit the other.

Restart Unimus, and the configuration should be applied.

On Linux (Debian/Ubuntu):

Edit the contents of **/etc/default/unimus**.

Add this into the file:

```
-Dserver.address=<your_ip> -Dserver.port=<port>
```

Insert proper values behind each configuration argument.

If you only want to configure a single parameter, please omit the other.

Restart Unimus, and the configuration should be applied.

Running in Tomcat:

Please refer to Tomcat documentation on configuring server port and bind-address.

How this is configured depends on the distribution and packaging of your Tomcat.